



# K 470 universal case, IP 65 - 366217

For all applications where extra leak-tightness and greater protection against moisture, water jets and dust is required.

## Product description

- For all applications where extra leak-tightness and greater protection against moisture, water jets and dust is required.
- Protection class IP 65 in accordance with EN 60 529 through foamed seal in the lid.
- 3 standard sizes ex stock, customised versions available on request.
- Also available with approval for the transportation of hazardous goods.
- Extra thick 1.5-mm sheet metal for all K470 containers from basic dimensions of 750 x 550 mm.
- Automatic pressure compensation membrane
- Leak-tightness verified with TÜV SÜD certificate.
- Available for most K 470 models.
- 3 standard sizes available from stock.




## Hints and special features

UN approval for the transportation of hazardous goods possible at additional charge.

Clearance measurement approx. 30mm (1.2") less than internal dimension (length and width). Special sizes on request.

## Product features

Colour of the stacking corners <b>Natural aluminium</b>	Corner beading <b>Yes</b>	Fasteners <b>Comfort fasteners</b>	Integrated wheels <b>No</b>	Internal dimensions L x W x H <b>750 mm x 550 mm x 380 mm</b>
Material	Material of the stacking	Max. gross weight	Number of handles	Outside dimensions



<b>Aluminium</b>	corners <b>Aluminium</b>	dangerous goods permission <b>102 kg</b>	<b>2</b>	max. L x W x H <b>800 mm x 600 mm x 410 mm</b>
Peripheral beading <b>Yes</b>	Protection class <b>IP65:</b>	Seal <b>foamed lid seal</b>	Stacking corners <b>Yes</b>	Volume <b>157 l</b>
Warranty <b>10 years</b>	Weight <b>10 kg</b>			