



K 470 universal case, IP 65 - 366218

For all applications where extra leak-tightness and greater protection against moisture, water jets and dust is required.

Product description

- For all applications where extra leak-tightness and greater protection against moisture, water jets and dust is required.
- Protection class IP 65 in accordance with EN 60 529 through foamed seal in the lid.
- 3 standard sizes ex stock, customised versions available on request.
- Also available with approval for the transportation of hazardous goods.
- Extra thick 1.5-mm sheet metal for all K470 containers from basic dimensions of 750 x 550 mm.
- Automatic pressure compensation membrane
- Leak-tightness verified with TÜV SÜD certificate.
- Available for most K 470 models.
- 3 standard sizes available from stock.



Hints and special features

UN approval for the transportation of hazardous goods possible at additional charge.

Clearance measurement approx. 30mm (1.2") less than internal dimension (length and width). Special sizes on request.

Product features

Colour of the stacking corners Natural aluminium	Corner beading Yes	Fasteners Comfort fasteners	Integrated wheels No	Internal dimensions L x W x H 750 mm x 550 mm x 580 mm
Material	Material of the stacking	Max. gross weight	Number of handles	Outside dimensions



Aluminium	corners Aluminium	dangerous goods permission 126 kg	2	max. L x W x H 800 mm x 600 mm x 610 mm
Peripheral beading Yes	Protection class IP65:	Seal foamed lid seal	Stacking corners Yes	Volume 239 l
Warranty 10 years	Weight 12 kg			