



Skyline 2E - 40206

Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.

Product description

- Easy and convenient vertical height adjustment makes this ladder ideal for use to access very great heights.
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Locks securely thanks to automatic spring loaded pawls.
- Top ladder section fitted with wall wheels.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Convenient rung-by-rung height adjustment, with wall wheels that will not damage the wall.

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	External width of lower ladder 490 mm	Load capacity max. 150 kg	Material Aluminium
Number of rungs 14	Number of rungs 2 x 14	Overall length, extended 7.21 m	Overall length, retracted 4.14 m	Pitch rung/tread 270 mm
Standards EN 131	Stile depth 85 mm	Stile depth 85mm	Transport dimensions approx. 4.150 mm	Tread depth 30 mm



professional			× approx. 520 mm × approx. 160 mm	
Type rung/tread serrated	Warranty 10 years	Weight 23 kg	Wheels Rubber	Wide crosspiece 1.2 m
Working height 7.9 m				