



Everest 2E - 40246

The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.

Product description

- The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.
- From length of 8.30 m – upper ladder with wheel assemblies. Wall wheels with wear-resistant surfaces that will not damage the wall.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 40245-40247
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- Both parts of the ladder can also be used separately as single ladders.
- Plastic anti-friction insert and lift-off retainer.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	External width of lower ladder 490 mm	Load capacity max. 150 kg	Material Aluminium
Number of rungs 8	Number of rungs 2 x 8	Overall length, extended 4.07 m	Overall length, retracted 2.39 m	Pitch rung/tread 270 mm
Standards EN 131	Stile depth 68 mm	Transport dimensions 2.390 mm x 500	Tread depth 30 mm	Type rung/tread serrated



professional		mm × 130 mm		
Warranty 10 years	Weight 9.8 kg	Wheels Rubber	Wide crosspiece 0.9 m	Working height 4.85 m