



Everest 2E - 40248

The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.

Product description

- The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.
- From length of 8.30 m – upper ladder with wheel assemblies. Wall wheels with wear-resistant surfaces that will not damage the wall.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 40245-40247
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- Plastic anti-friction insert and lift-off retainer.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	External width of lower ladder 490 mm	Load capacity max. 150 kg	Material Aluminium
Number of rungs 12	Number of rungs 2 x 12	Overall length, extended 6.09 m	Overall length, retracted 3.56 m	Pitch rung/tread 270 mm
Standards EN 131 professional	Stile depth 73 mm	Transport dimensions 3.570 mm x 500 mm x 160 mm	Tread depth 30 mm	Type rung/tread serrated



Warranty	Weight	Wheels	Wide crosspiece	Working height
10 years	18 kg	Rubber	1.1 m	6.8 m