

# Mobile platform steps with ZARGES Ergo Stop - 40255022




Mobile access or work platforms that offer comfortable ascent. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

## Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Individually adjustable platform lengths.
- Platform steps instantly ready for use due to an innovative brake system.
- Chassis available in a non-static version as an option.
- ZARGES Ergo Stop - all four castors can be braked conveniently using the footpedal on the flight of steps.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.

## Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall



protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.

Standard applied: DIN EN ISO 14122.

## Product features

|                                 |                                  |                                     |                                      |                                   |
|---------------------------------|----------------------------------|-------------------------------------|--------------------------------------|-----------------------------------|
| Chassis width<br><b>1220 mm</b> | Inclination<br><b>45 °</b>       | Load capacity<br><b>max. 300 kg</b> | Max. load per tread<br><b>150 kg</b> | Number of treads<br><b>12</b>     |
| Overall span<br><b>3447 mm</b>  | Platform length<br><b>600 mm</b> | Standards<br><b>EN ISO 14122</b>    | Tread width<br><b>600 mm</b>         | Vertical height<br><b>2790 mm</b> |
| Warranty<br><b>10 years</b>     |                                  |                                     |                                      |                                   |