

More information about the product, accessories and spare parts: https://www.zarges.com/en/products/mobile-platform-steps-with-zarges-ergostop-40255050



Mobile platform steps with ZARGES Ergo Stop -40255050

Mobile access or work platforms that offer comfortable ascent. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Individually adjustable platform lengths.
- Platform steps instantly ready for use due to an innovative brake system.
- Chassis available in a non-static version as an option.
- ZARGES Ergo Stop all four castors can be braked conveniently using the footpedal on the flight of steps.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.

Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall







protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection. Standard applied: DIN EN ISO 14122.

Product features

| Chassis width | Inclination | Load capacity | Max. load per tread | Number of treads |
|---------------|-----------------|---------------|---------------------|------------------|
| 1620 mm | 45 ° | max. 300 kg | 150 kg | 20 |
| 0 " | | | T 1.10 | |
| Overall span | Platform length | Standards | Tread width | Vertical height |
| 5167 mm | 600 mm | EN ISO 14122 | 800 mm | 4510 mm |
| | | | | |
| | | | | |

Warranty

10 years