




Mobile access steps with platform - 40255754

Mobile access or work platforms that offer comfortable ascent. Ideal for work over long periods, even with tools and frequent changes of working position. Large-area platform with guardrail for safe and ergonomic working at heights.

Product description

- Different angles of inclination, 45° for comfortable access, 60° for confined spaces.
- Serrated aluminium (R10) step and platform surfaces as standard. Also available as steel open grid (R12) and steel perforated plate (R13) for extra non-slip properties.
- Selection of tread widths 600 mm, 800 mm or 1000 mm.
- Individually adjustable platform lengths.
- Cantilever platform available for bridging obstacles.
- Chassis available in a non-static version as an option.
- Narrow chassis. The chassis width is reduced to a minimum through additional ballasting.
- Individual guardrail configuration on the platform, optionally with swing door or pole barrier.
- Maximum flexibility with optional handrails and guardrails which can be removed without tools.
- Quick and simple assembly with the ZARGES connection system with a high level of pre-assembly.



Hints and special features

We recommend equipping the product in accordance with the German Equipment and Product Safety Act (ProdSG) with two-sided handrails and, for steps with platforms or maintenance platforms, all-round fall protection (e.g. guardrails). If handrails or guardrails are not desired, the operator must ensure sufficient regulatory protection.



Standard applied: DIN EN ISO 14122.

Product features

Chassis width 1420 mm	Inclination 60 °	Load capacity max. 300 kg	Max. load per tread 150 kg	Number of treads 14
Overall span 2720 mm	Platform length 600 mm	Standards EN ISO 14122	Tread width 1000 mm	Vertical height 3750 mm
Warranty 10 years				