



## Coni B - 40275

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

### Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Step ladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

### Product features

Anti splay <b>Belt strap</b>	Base <b>0,93 m × 0,51 m</b>	Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminium</b>	Number of rungs <b>5</b>	Number of rungs <b>2 × 5</b>	Overall base width <b>0.51 m</b>	Overall length <b>1.53 m</b>
Pitch rung/tread <b>265 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>58 mm</b>	Transport dimensions <b>1.530 mm × 510 mm × 170 mm</b>	Tread depth <b>30 mm</b>



Type rung/tread <b>serrated</b>	Vertical ladder height <b>1.46 m</b>	Warranty <b>10 years</b>	Weight <b>5.8 kg</b>	Working height <b>2.75 m</b>
------------------------------------	---	-----------------------------	-------------------------	---------------------------------