



Coni B - 40277

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Step ladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

Product features

| | | | | |
|-----------------------------------|---|---------------------------------|---|-------------------------------------|
| Anti splay Belt strap | Base 1,22 m x 0,57 m | Coating natural | Connection Stile-Rung flanged | Load capacity max. 150 kg |
| Material Aluminium | Number of rungs 7 | Number of rungs 2 x 7 | Overall base width 0.57 m | Overall length 2.09 m |
| Pitch rung/tread 265 mm | Standards EN 131 professional | Stile depth 58 mm | Transport dimensions approx. 2.090 mm x 570 mm x approx. 170 mm | Tread depth 30 mm |
| | | | | |



| | | | | |
|------------------------------------|---|-----------------------------|-------------------------|---------------------------------|
| Type rung/tread serrated | Vertical ladder height 1.99 m | Warranty 10 years | Weight 7.3 kg | Working height 3.25 m |
|------------------------------------|---|-----------------------------|-------------------------|---------------------------------|