



# Coni B - 40316

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

## Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



## Hints and special features

Stepladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

## Product features

Anti splay <b>Belt strap</b>	Base <b>2,54 m x 0,84 m</b>	Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminium</b>	Number of rungs <b>16</b>	Number of rungs <b>2 x 16</b>	Overall base width <b>0.84 m</b>	Overall length <b>4.61 m</b>
Pitch rung/tread <b>265 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>68 mm</b>	Transport dimensions <b>approx. 4.610 mm x approx. 840 mm x approx. 190 mm</b>	Tread depth <b>30 mm</b>



Type rung/tread <b>serrated</b>	Vertical ladder height <b>4.45 m</b>	Warranty <b>10 years</b>	Weight <b>21.2 kg</b>	Working height <b>5.65 m</b>
------------------------------------	---	-----------------------------	--------------------------	---------------------------------