



Coni B - 40320

Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.

Product description

- Whenever you need access to great heights: flexibility with up to 20 rungs for working heights of up to 6.70 m.
- Sturdy aluminium alloy rungs (30 x 30 mm) with non-slip serrated surface.
- Sturdy, solidly screwed steel hinges
- Two high-strength Perlon belts, secured without twisting to the rung, prevent splay.
- High strength, non-twist rung/stile connections.
- Additional stabilisation by bracing on the bottom rung.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Step ladder for maximum working heights of up to 6.70 m.

Complies with EN 131 Professional.

Product features

Anti splay Belt strap	Base 2,84 m x 0,9 m	Coating natural	Connection Stile-Rung flanged	Load capacity max. 150 kg
Material Aluminium	Number of rungs 18	Number of rungs 2 x 18	Overall base width 0.9 m	Overall length 5.17 m
Pitch rung/tread 265 mm	Standards EN 131 professional	Stile depth 73 mm	Transport dimensions approx. 5.170 mm x approx. 900 mm x approx. 200 mm	Tread depth 30 mm



Type rung/tread serrated	Vertical ladder height 5 m	Warranty 10 years	Weight 25.6 kg	Working height 6.15 m
------------------------------------	--------------------------------------	-----------------------------	--------------------------	---------------------------------