



# Seventec B - 40357

Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.

## Product description

- Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.
- Treads 85 mm deep for safe standing.
- Sturdy hinged connection integrated in the treads.
- Optimal stability thanks to the fold-down locking bar on both sides.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Non-slip plastic end caps.



## Hints and special features

Complies with EN 131 Professional.

## Product features

|  |   |                                  |   |                                     |
|--|---|----------------------------------|---|-------------------------------------|
| Anti splay<br><b>Rigid locking bar</b> | Base<br><b>1,34 m × 0,5 m</b>           | Coating<br><b>natural</b>        | Connection Stile-Rung<br><b>riveted</b>                   | Load capacity<br><b>max. 150 kg</b> |
| Material<br><b>Aluminium</b>           | Number of treads<br><b>7</b>            | Number of treads<br><b>2 × 7</b> | Overall base width<br><b>0.5 m</b>                        | Overall length<br><b>1.66 m</b>     |
| Pitch rung/tread<br><b>218 mm</b>      | Standards<br><b>EN 131 professional</b> | Stile depth<br><b>87 mm</b>      | Transport dimensions<br><b>1.660 mm × 500 mm × 230 mm</b> | Tread depth<br><b>85 mm</b>         |
| Type rung/tread<br><b>serrated</b>     | Vertical ladder height<br><b>1.53 m</b> | Warranty<br><b>10 years</b>      | Weight<br><b>10.5 kg</b>                                  | Working height<br><b>3.1 m</b>      |