



Seventec B - 40358

Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.

Product description

- Stable and comfortable: deep treads for safe standing, smooth stiles that are comfortable to hold.
- Treads 85 mm deep for safe standing.
- Sturdy hinged connection integrated in the treads.
- Optimal stability thanks to the fold-down locking bar on both sides.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Non-slip plastic end caps.

Hints and special features

Complies with EN 131 Professional.

Product features



Anti splay	Base	Coating	Connection Stile-Rung	Load capacity
Rigid locking bar	1,5 m × 0,52 m	natural	riveted	max. 150 kg
Material	Number of treads	Number of treads	Overall base width	Overall length
Aluminium	8	2 × 8	0.52 m	1.9 m
Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth
218 mm	EN 131 professional	87 mm	1.890 mm × 530 mm × 230 mm	85 mm
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height
serrated	1.74 m	10 years	12 kg	3.35 m

Tel: +49 (0)881-687-100www.zarges.comFax: +49 (0)881-687-500zarges@zarges.deSubject to change or error.