



# W 172 trolley - 40634

Sturdy aluminium trolley for versatile use.

## Product description

- Sturdy aluminium trolley for a wide variety of applications.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to side walls and base.
- One of the long sides has a cut-out section measuring approx. 1,230 x 295 mm for convenient loading and unloading.
- End and side walls reinforced with peripheral beading and corner beads.
- One sliding handle at either end.
- Sturdy, generously dimensioned edge and base profile sections, high-strength positive locking ensures permanent bonding to jacket and base metal.
- One long side with cutout section, approx. 1.230 x 295 mm.
- Side cutout with profile-section surround; profile-section joints continuously welded.
- Chassis: 2 swivel and 2 fixed castors - corner-mounted, Ø 200 mm, 40 mm wide, easy-running, rubber wheels, "non-marking", roller bearings, thread guards.



## Product features

<p>Formation Chassis</p> <p><b>2 swivel and 2 fixed castors mounted at the corners</b></p>	<p>Internal dimensions L x W x H</p> <p><b>1.500 mm x 900 mm x 700 mm</b></p>	<p>Material</p> <p><b>Aluminium</b></p>	<p>Outside dimensions max. L x W x H</p> <p><b>1.650 mm x 950 mm x 980 mm</b></p>	<p>Peripheral beading</p> <p><b>Yes</b></p>
<p>Volume</p> <p><b>945 l</b></p>	<p>Weight</p> <p><b>37 kg</b></p>	<p>Wheel diameter</p> <p><b>200 mm</b></p>		