



Skyline EFA 2E - 41276

For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.

Product description

- For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Wall wheels that will not damage the wall.
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Overall width of bottom section: 430 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

External width of lower ladder	Load capacity	Material	Number of rungs	Number of rungs
420 mm	max. 150 kg	Glass-fibre reinforced plastic	16	2 x 16



Overall length, extended 7.72 m	Overall length, retracted 4.64 m	Pitch rung/tread 270 mm	Standards EN 131 professional	Stile depth 90 mm
Transport dimensions 4.650 mm × 450 mm × 150 mm	Tread depth 30 mm	Type rung/tread serrated	Warranty 10 years	Weight 41.3 kg
Wheels Rubber	Wide crosspiece 1.2 m	Working height 8.5 m		