



# Skymaster X - 41542

Convertible to take on challenging tasks with greater safety.

## Product description

- Convertible to take on challenging tasks with greater safety.
- Can be used on steps/stairs for Order Nos. 41536-41540.
- One rigid connection.
- Upper ladder can also be used separately as single ladders (Order No. 41536-41540).
- Cannot be used on stairs.
- Strong Perlon straps.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



## Hints and special features

Complies with EN 131 Professional.

## Product features

|   |   |   |   |                                     |
|---|---|---|---|-------------------------------------|
| Coating<br><b>natural</b>               | Connection Stile-Rung<br><b>flanged</b> | Ladder length as 3-part single ladder<br><b>8.6 m</b> | Length as 2-part single ladder and as stepladder with push-on section<br><b>6.1 m</b> | Load capacity<br><b>max. 150 kg</b> |
| Material<br><b>Aluminium</b>            | Number of rungs<br><b>12</b>            | Number of rungs<br><b>3 x 12</b>                      | Overall length, retracted<br><b>3.55 m</b>  | Pitch rung/tread<br><b>265 mm</b>   |
| Rigid locking bar<br><b>on one side</b> | Standards<br><b>EN 131 professional</b> | Stile depth<br><b>98 mm</b>                           | Transport dimensions<br><b>3.590 mm x 500 mm x 230 mm</b>                             | Tread depth<br><b>30 mm</b>         |



| Type rung/tread<br><b>serrated</b> | Warranty<br><b>10 years</b> | Weight<br><b>30.1 kg</b> | Wide crosspiece<br><b>1.2 m</b> | Working height as 3-part single ladder<br><b>9.35 m</b> |
|------------------------------------|-----------------------------|--------------------------|---------------------------------|---|