



R13step B - 41549

The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.

Product description

- The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.
- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay Belt strap	Base 0,79 m × 0,44 m	Coating anodised	Connection Stile-Rung flanged	Load capacity max. 150 kg
Material Aluminium	Number of treads 3	Number of treads 2 × 3	Overall base width 0.44 m	Overall length 0.88 m
Pitch rung/tread 265 mm	Standards EN 131 professional	Stile depth 73 mm	Transport dimensions approx. 880 mm × approx. 450 mm × approx. 220 mm	Tread depth 80 mm
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height



R13 tread

0.8 m

10 years

5.8 kg

2.3 m