




# R13step B - 41551

The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.

## Product description

- The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.
- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



## Hints and special features

Complies with EN 131 Professional.



## Product features

Anti splay <b>Belt strap</b>	Base <b>0,98 m x 0,47 m</b>	Coating <b>anodised</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminium</b>	Number of treads <b>4</b>	Number of treads <b>2 x 4</b>	Overall base width <b>0.47 m</b>	Overall length <b>1.15 m</b>
Pitch rung/tread <b>265 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>73 mm</b>	Transport dimensions <b>approx. 1.155 mm x approx. 475 mm x approx. 220 mm</b>	Tread depth <b>80 mm</b>
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height



**R13 tread**

**1.06 m**

**10 years**

**7.2 kg**

**2.55 m**