






# R13step B - 41565

The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.

## Product description

- The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.
- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



## Hints and special features

Complies with EN 131 Professional.



## Product features

Anti splay <b>Belt strap</b>	Base <b>2,95 m × 0,77 m</b>	Coating <b>anodised</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminium</b>	Number of treads <b>14</b>	Number of treads <b>2 × 14</b>	Overall base width <b>0.77 m</b>	Overall length <b>3.95 m</b>
Pitch rung/tread <b>265 mm</b>	Standards <b>EN 131 professional</b>	Stile depth <b>73 mm</b>	Transport dimensions <b>approx. 3.950 mm × approx. 770 mm × approx. 220 mm</b>	Tread depth <b>80 mm</b>
Type rung/tread	Vertical ladder height	Warranty	Weight	Working height



**R13 tread**

**3.67 m**

**10 years**

**22.6 kg**

**5.2 m**