



## R13step B - 41567

The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.

### Product description

- The ladder with the highest non-slip performance thanks to R13 treads for oily and wet environments.
- 80 mm deep treads with R13 surface and perforations to drain fast.
- Abrasion-resistant, anodised stiles.
- Hinges of diecast aluminium.
- High-strength perlon belts prevent splay.
- Maximum working heights thanks to 280mm high access.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



### Hints and special features

Complies with EN 131 Professional.

### Product features

Anti splay <b>Belt strap</b>	Base <b>3,34 m × 0,83 m</b>	Coating <b>anodised</b>	Connection Stile-Rung <b>flanged</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminium</b>	Number of treads <b>16</b>	Number of treads <b>2 × 16</b>	Overall base width <b>0.83 m</b>	Overall length <b>4.51 m</b>
Pitch rung/tread	Standards	Stile depth	Transport dimensions	Tread depth



<b>265 mm</b>	<b>EN 131 professional</b>	<b>73 mm</b>	<b>approx. 4.510 mm × approx. 830 mm × approx. 220 mm</b>	<b>80 mm</b>
Type rung/tread <b>R13 tread</b>	Vertical ladder height <b>4.21 m</b>	Warranty <b>10 years</b>	Weight <b>26.6 kg</b>	Working height <b>5.7 m</b>