

Skymaster Plus X - 41580

One ladder, many functions: the flexible solution for accessing higher places safely and providing extra stability. The ladder is particularly safe and comfortable to use due to the 80 mm deep treads on the upper ladder.

Product description

- One ladder, many functions: the flexible solution for accessing higher places safely and providing extra stability. The ladder is particularly safe and comfortable to use due to the 80 mm deep treads on the upper ladder.
- Particularly light thanks to the combination of stepladder and rung ladder (hybrid design).
- Maximum stability thanks to rigid connection on both sides.
- The horizontal stabiliser bar is fitted with castors for ergonomic transport.
- Upper ladder with top wheel assembly.
- Upper ladder can also be used separately as single ladders for Order Nos. 41578-41579.
- Strong Perlon straps.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Lift-off retainer and guides are bolted in so that they can be replaced.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.




Hints and special features

Optimum stability due to extra-wide horizontal stabiliser bar and two rigid locking bars.

Complies with EN 131 Professional.

Product features



Coating natural	Connection Stile-Rung flanged	Ladder length as 3-part single ladder 8.61 m	Length as 2-part single ladder and as stepladder with push-on section 6.1 m	Load capacity max. 150 kg
Material Aluminium	Number of rungs 12	Number of rungs 3 × 12	Overall length, retracted 3.58 m	Pitch rung/tread 265 mm
Rigid locking bar on both sides	Standards EN 131 professional	Stile depth 98 mm	Transport dimensions approx. 3.585 mm × approx. 500 mm × approx. 245 mm	Type rung/tread serrated
Warranty 10 years	Weight 32.1 kg	Wheels Rubber	Wide crosspiece 1.2 m	Working height as 3- part single ladder max. approx. 9.15 m