



# Varioflex B - 41936

Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.

## Product description

- Special ladder that ensures safe standing even when working on uneven ground, on steps and overhangs.
- Continuous adjustment to the millimetre. Each individual stile of the ladder locks securely by the turn of a handle.
- Stile dimensions: 60 x 24 mm.
- Rungs and stiles made from extruded aluminium sections.
- High strength, non-twist rung/stile connections.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping and at the same time provide firm seating in the stile.



## Hints and special features

Ideal for applications in difficult terrain.  
 Complies with EN 131 Professional.



## Product features

Additional adjustment range on ladder section <b>0.4 m</b>	Additional adjustment range on support section <b>1.3 m</b>	Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Length excluding extension <b>1.8 m</b>
Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>	Number of rungs <b>6</b>	Number of rungs <b>2 x 6</b>	Pitch rung/tread <b>265 mm</b>
Transport dimensions <b>1.850 mm x 600 mm x 140 mm</b>	Tread depth <b>30 mm</b>	Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>	Weight <b>12.5 kg</b>
Working height				



3 m