



# Mobile access steps with platform, single-sided access, with steel open-grid treads and platform - 41954

The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.

## Product description

- The flexible access solution with open-grid treads for improved non-slip performance in wet-room applications.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through platform railing at a height of 1.00 m on three sides.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



## Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

## Product features

|                                |                           |  |                                    |                                     |
|--------------------------------|---------------------------|--|------------------------------------|-------------------------------------|
| Base<br><b>0,93 m × 1,81 m</b> | Coating<br><b>natural</b> | Connection Stile-Rung<br><b>welded</b> | Guardrail height<br><b>1000 mm</b> | Load capacity<br><b>max. 150 kg</b> |
| Material                       | Number of rungs, incl.    | Pitch rung/tread                       | Platform height                    | Platform length                     |



|                                   |                              |   |                              |   |
|-----------------------------------|------------------------------|---|------------------------------|---|
| <b>Aluminum/steel, galvanised</b> | platform<br><b>6</b>         | <b>240 mm</b>   | <b>1.44 m</b>                | <b>800 mm</b>                               |
| Platform width<br><b>600 mm</b>   | Standards<br><b>EN 131-7</b> | Transport dimensions<br><b>1.820 mm × 930 mm × 350 mm</b> | Tread depth<br><b>200 mm</b> | Type rung/tread<br><b>Open-grid surface</b> |
| Warranty<br><b>10 years</b>       | Weight<br><b>59.7 kg</b>     | Working height<br><b>3.45 m</b>                           |                              |   |