



# Mobile access steps with platform, double-sided access, with light-alloy treads and platform - 41986

Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.

## Product description

- Maximum flexibility while ascending and descending, larger working area on the treads and four sprung castors for a high degree of mobility and stability.
- Quick and easy assembly thanks to the new connecting elements.
- Mobile and ready for operation in no time with four sprung swivel castors (two of each with brakes).
- Maximum safety through double-sided platform railing at a height of 1.00 m.
- Comfortable ascent through treads with a depth of 200 mm.
- Spacious platform, 600 x 800 mm.
- Maximum loading capacity 150 kg.



## Hints and special features

Double-sided handrail in accordance with EN 131-7 on access optional.

Complies with EN 131-7

## Product features

Base <b>1,03 m x 2,9 m</b>	Coating <b>natural</b>	Connection Stile-Rung <b>welded</b>	Guardrail height <b>1000 mm</b>	Load capacity <b>max. 150 kg</b>
Material	Number of rungs, incl.	Number of treads	Pitch rung/tread	Platform height



<b>Aluminium</b>	platform <b>2 x 8</b>	<b>8</b>	<b>240 mm</b>	<b>1.92 m</b>
Platform length <b>800 mm</b>	Platform width <b>600 mm</b>	Standards <b>EN 131-7</b>	Transport dimensions <b>2.820 mm x 1.120 mm x 410 mm</b>	Tread depth <b>200 mm</b>
Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>	Weight <b>57.5 kg</b>	Working height <b>3.9 m</b>	