



Nova S - 42457

The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.

Product description

- The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.
- Large platform with anti-slip ribbing.
- Practical tray with plenty of space for tools and small items.
- 80 mm deep surfaces to stand on.
- High-strength perlon belts prevent splay.
- Patented tread construction: robust, stable, durable, flanged rung-stile connection.
- The extruded aluminium sections give the platform optimum stability.
- Two extruded section bridge raisers.
- Firm positioning thanks to anti-slip plastic end caps.
- Enclosed rung profile and integrated guide tube.



Hints and special features

Complies with EN 131 Professional.

Product features

Anti splay Belt strap	Base 1,28 m × 0,51 m	Coating natural	Connection Stile-Rung flanged	Load capacity max. 150 kg
Material Aluminium	Number of rungs, incl. platform 7	Overall base width 0.51 m	Overall length 2.26 m	Pitch rung/tread 216 mm
Platform height 1.48 m	Platform length 250 mm	Platform width 250 mm	Standards EN 131 professional	Stile depth 48 mm



Stile depth 48 mm	Stile depth steps/back stay 48mm / 48mm	Transport dimensions 2.270 mm × 520 mm × 120 mm	Tray Plastic	Tread depth 80 mm
Type rung/tread serrated	Vertical ladder height 2.08 m	Warranty 10 years	Weight 9.1 kg	Working height 3.5 m