



Nova S - 42458

The classic model for safe standing and comfortable working, with a practical storage tray and high-stability patented rung-stile connection.

Product description

- The classic model for safe standing and comfortable working, with a practical storage tray and highstability patented rung-stile connection.
- · Large platform with anti-slip ribbing.
- Practical tray with plenty of space for tools and small items
- 80 mm deep surfaces to stand on.
- High-strength perlon belts prevent splay.
- Patented tread construction: robust, stable, durable, flanged rung-stile connection.
- The extruded aluminium sections give the platform optimum stability.
- Two extruded section bridge raisers.
- Firm positioning thanks to anti-slip plastic end caps.
- Enclosed rung profile and integrated guide tube.

Hints and special features

Complies with EN 131 Professional.

Product features

| Anti splay Belt strap | Base 1,44 m × 0,54 m | Coating natural | Connection Stile-Rung flanged | Load capacity max. 150 kg |
|------------------------|---------------------------------|----------------------------|-------------------------------|---------------------------|
| Material Aluminium | Number of rungs, incl. platform | Overall base width 0.54 m | Overall length 2.49 m | Pitch rung/tread 216 mm |
| Platform height 1.7 m | Platform length 250 mm | Platform width 250 mm | Standards EN 131 professional | Stile depth 48 mm |



82362 Weilheim







| Stile depth | Stile depth steps/back stay | Transport dimensions | Tray | Tread depth |
|-----------------|-----------------------------|-------------------------------|---------|----------------|
| 48 mm | 48mm / 48mm | 2.500 mm × 540 mm × 120 mm | Plastic | 80 mm |
| Type rung/tread | Vertical ladder height | Warranty | Weight | Working height |
| serrated | 2.29 m | 10 years | 10.2 kg | 3.7 m |