



Everest 2DE - 44820

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Robust extruded-section triangular rungs with step horizontal in working position.
- Both parts of the ladder can also be used separately as single ladders.
- External width of lower ladder: 420 mm.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

| | | | | |
|---|---|---|--|------------------------------------|
| Coating natural | Connection Stile-Rung flanged | External width of lower ladder 420 mm | Load capacity max. 150 kg | Material Aluminium |
| Number of rungs 10 | Number of rungs 2 x 10 | Overall length, extended 4.93 m | Overall length, retracted 2.98 m | Pitch rung/tread 265 mm |
| Standards EN 131 professional | Stile depth 68 mm | Transport dimensions 2.980 mm x 430 mm x 120 mm | Tread depth 38 mm | Type rung/tread serrated |
| Warranty | Weight | Wide crosspiece | Working height | |



10 years

11.3 kg

0.9 m

5.65 m