



# Everest 2DE - 44828

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

## Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Robust extruded-section triangular rungs with step horizontal in working position.
- External width of lower ladder: 420 mm.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



## Hints and special features

Complies with EN 131 Professional.

## Product features

|                                         |                                         |                                                           |                                            |                                    |
|-----------------------------------------|-----------------------------------------|-----------------------------------------------------------|--------------------------------------------|------------------------------------|
| Coating<br><b>natural</b>               | Connection Stile-Rung<br><b>flanged</b> | External width of lower ladder<br><b>420 mm</b>           | Load capacity<br><b>max. 150 kg</b>        | Material<br><b>Aluminium</b>       |
| Number of rungs<br><b>18</b>            | Number of rungs<br><b>2 × 18</b>        | Overall length, extended<br><b>9.17 m</b>                 | Overall length, retracted<br><b>5.23 m</b> | Pitch rung/tread<br><b>265 mm</b>  |
| Standards<br><b>EN 131 professional</b> | Stile depth<br><b>85 mm</b>             | Transport dimensions<br><b>5.230 mm × 430 mm × 145 mm</b> | Tread depth<br><b>38 mm</b>                | Type rung/tread<br><b>serrated</b> |
| Warranty<br><b>10 years</b>             | Weight<br><b>23.9 kg</b>                | Wide crosspiece<br><b>1.2 m</b>                           | Working height<br><b>9.8 m</b>             |                                    |