



# Everest 2DE - 44834

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

## Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Robust extruded-section triangular rungs with step horizontal in working position.
- Both parts of the ladder can also be used separately as single ladders.
- External width of lower ladder: 420 mm.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	External width of lower ladder <b>420 mm</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>
Number of rungs <b>8</b>	Number of rungs <b>2 x 8</b>	Overall length, extended <b>3.8 m</b>	Overall length, retracted <b>2.42 m</b>	Pitch rung/tread <b>265 mm</b>
Standards <b>EN 131 professional</b>	Stile depth <b>58 mm</b>	Transport dimensions <b>2.420 mm x 420 mm x 115 mm</b>	Tread depth <b>38 mm</b>	Type rung/tread <b>serrated</b>
Warranty	Weight	Wide crosspiece	Working height	



**10 years**

**9.3 kg**

**0.8 m**

**4.6 m**