



Skymaster DX - 44837

The basic version offers high functionality and flexibility and an excellent price/performance ratio.

Product description

- The basic version offers high functionality and flexibility and an excellent price/performance ratio.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Upper ladder can also be used separately as single ladders.
- Strong Perlon straps.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung flanged	Ladder length as 3-part single ladder 4.4 m	Length as 2-part single ladder and as stepladder with push-on section 3.25 m	Load capacity max. 150 kg
Material Aluminium	Number of rungs 7	Number of rungs 3 x 7	Overall length, retracted 2.14 m	Pitch rung/tread 265 mm
Standards EN 131 professional	Stile depth 58 mm	Transport dimensions 2.130 mm x 500 mm x 170 mm	Tread depth 38 mm	Type rung/tread serrated
Warranty	Weight	Wide crosspiece	Working height as 3-part	



10 years

13.8 kg

0.8 m

single ladder

5.2 m