



Skymaster DX - 44839

The basic version offers high functionality and flexibility and an excellent price/performance ratio.

Product description

- The basic version offers high functionality and flexibility and an excellent price/performance ratio.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Upper ladder can also be used separately as single ladders.
- Strong Perlon straps.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



Hints and special features

Complies with EN 131 Professional.

Product features

| | | | | |
|---|---|---|---|-------------------------------------|
| Coating natural | Connection Stile-Rung flanged | Ladder length as 3-part single ladder 6.1 m | Length as 2-part single ladder and as stepladder with push-on section 4.4 m | Load capacity max. 150 kg |
| Material Aluminium | Number of rungs 9 | Number of rungs 3 x 9 | Overall length, retracted 2.7 m | Pitch rung/tread 265 mm |
| Standards EN 131 professional | Stile depth 73 mm | Transport dimensions 2.690 mm x 500 mm x 190 mm | Tread depth 38 mm | Type rung/tread serrated |
| Warranty | Weight | Wide crosspiece | Working height as 3-part | |



10 years

18 kg

1 m

single ladder

6.85 m