



# Skymaster DX - 44842

The basic version offers high functionality and flexibility and an excellent price/performance ratio.

## Product description

- The basic version offers high functionality and flexibility and an excellent price/performance ratio.
- Upper ladder can also be used separately as single ladders for Order Nos. 44837-44840.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Strong Perlon straps.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.
- Cannot be used on stairs.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	Ladder length as 3-part single ladder <b>8.3 m</b>	Length as 2-part single ladder and as stepladder with push-on section <b>5.8 m</b>	Load capacity <b>max. 150 kg</b>
Material <b>Aluminium</b>	Number of rungs <b>12</b>	Number of rungs <b>3 × 12</b>	Overall length, retracted <b>3.54 m</b>	Pitch rung/tread <b>265 mm</b>
Standards <b>EN 131 professional</b>	Stile depth <b>85 mm</b>	Transport dimensions <b>3.550 mm × 500 mm × 220 mm</b>	Tread depth <b>38 mm</b>	Type rung/tread <b>serrated</b>
Warranty	Weight	Wide crosspiece	Working height as 3-part single ladder	



**10 years**

**25.9 kg**

**1.2 m**

**9 m**