



Mitraset Classic 19" case

- 45805

Housing for electronic instruments

Product description

- Protection against mechanical stresses such as impacts, shocks or vibrations. Protection against electromagnetic interference (such as radio waves or lightning strikes) is also available as an option.
- Protection against environmental influences such as heat, moisture, water or dust.
- For loads of up to 100 kg.
- 3 - 22 height units, nominal depth 219 - 990 mm.
- Housings with nominal depths 219 mm, 350 mm and 480 mm can be stacked together.
- Elastically susp. anti-vibration frame.
- Stacking segments on housing top and bottom.
- Recesses on side walls for drop handles.
- Recess also suitable for accommodating protective pressure compensation valves and humidity indicator.
- Standard housing with additional reinforced specifications.
- Lid with toggle-action snap fasteners.
- IP 65 rated
- Fulfils the requirements of VG 95447.
- Tested according to AECTP standards.
- Tested according to MIL-STD-810.
- Modified version with testing in accordance with MIL-STD-810 F.
- Shielding attenuation test in accordance with MIL-STD-285.
- Customised versions available.



Hints and special features

Additional sizes available on request. Height of casing with stacking foot = external dimension (nominal size) + 11.5mm. Depth of special lid varies according to design.



Also available as UN-approved hazardous goods packaging.

Comprehensive range of special fittings for many applications.

Product features

Installation height	Nominal depth	Outside dimensions max. L x W x H	Weight
5 HE/U	610 mm	704 mm x 534 mm x 303,5 mm	14.7 kg