



CompactMaster S-PLUS

1T - 53121

The top-selling folding scaffold unit is now available with advanced guardrail and two metre platform distance for safe and fast erection.

Product description

- The top-selling folding scaffold unit is now available with advanced guardrail and two metre platform distance for safe and fast erection.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding width: 0.85 m (to the outside edge of folding unit hinge); scaffolding length: 1.80 m.
- Working heights can be extended from 3.75 m to max. 13.55 m with standard parts.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.
- Standard castors: height-adjustable 150 mm swivel castors (order no. 42759) for millimetre-perfect level adjustment.



Product features

Claw type automatic	Height-adjustable castors: Yes	Overall height 3.85 m	Platform height 2.6 m	Platform length 1.8 m
Platform length 1.8 m	Platform size 0,6m x 1,8m	Platform width 0.6 m	Rung diameter 50 mm	Scaffolding class 3 (= 200 kg/m²)
Standards EN 1004-1	Stile diameter 50 mm	Transport dimensions 0 mm0 mm0 mm	Warranty 10 years	Weight 123.6 kg
Wheel diameter 150 mm	Width scaffolding 0.85 m	Working height 4.6 m		