


# CompactMaster S-PLUS

## 1T - 53181

The top-selling folding scaffold unit is now available with advanced guardrail and two metre platform distance for safe and fast erection.

### Product description

- The top-selling folding scaffold unit is now available with advanced guardrail and two metre platform distance for safe and fast erection.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding width: 0.85 m (to the outside edge of folding unit hinge); scaffolding length: 1.80 m.
- Working heights can be extended from 3.75 m to max. 13.55 m with standard parts.
- Scaffolding category 3 (maximum load of 200 kg/m<sup>2</sup>) according to DIN EN 1004.
- Standard castors: height-adjustable 150 mm swivel castors (order no. 42759) for millimetre-perfect level adjustment.



### Product features

Claw type <b>automatic</b>	Height-adjustable castors: <b>Yes</b>	Overall height <b>9.7 m</b>	Platform height <b>8.4 m</b>	Platform length <b>1.8 m</b>
Platform length <b>1.8 m</b>	Platform size <b>0,6m x 1,8m</b>	Platform width <b>0.6 m</b>	Rung diameter <b>50 mm</b>	Scaffolding class <b>3 (= 200 kg/m<sup>2</sup>)</b>
Standards <b>EN 1004-1</b>	Stile diameter <b>50 mm</b>	Transport dimensions <b>0 mm0 mm0 mm</b>	Warranty <b>10 years</b>	Weight <b>249.6 kg</b>
Wheel diameter <b>150 mm</b>	Width scaffolding <b>0.85 m</b>	Working height <b>10.45 m</b>		