



K 424 XC Mobile Box

The new K 424 XC combines the legendary quality of ZARGES cases with new mobility.

Product description

- The K 424 XC has excellent mobility and ergonomics owing to its integrated wheels and pull-out handles (for order no. 41810-41814) or second sprung drop handle on the end face (for order no. 41815).
- All-round beading and corner beading offer additional stability, allowing the box to withstand a load of up to 50 kg despite its low weight.
- Stackability guaranteed through stacking corners made from impact-resistant plastic and integrated stacking elements in the support frame. Can also be stacked with containers in the ZARGES K 470 and Eurobox series.
- Can be fitted with an optional 125 mm wheel set or 220 mm off-road wheel set (for models with a volume of 60 litres and above) to improve its mobility on difficult terrain.
- Sturdy, mobile aluminium box in ZARGES quality, long service life, a reliable companion.
- Optimum mobility through integrated 50 mm castors and pull-out handle (Order No. 41810-41814) or second sprung drop handle on the end face (Order No. 41815).
- Extremely smooth-running due to special castors, ø
 50 mm, made from polyurethane and polyamide.
- ZARGES Comfort fasteners with extremely long service life, fitted with plug locks.
- High load-bearing capacity of up to 50 kg despite the low dead weight.
- UN approval for the transportation of hazardous goods possible at additional charge.
- Optional wheel set 125 mm or off-road set 220 mm available for use in difficult terrain.
- Beading all round and corner beads for additional









82362 Weilheim





dimensional stability.

- · A wide range of adjustable interior fittings ensure versatility.
- Peripheral foamed seal in the lid for protection against dust and splashwater.

Hints and special features

Clearance measurement approx. 30mm (1.2") less than internal dimension (length and width). Special sizes on request.

Product features

Colour of the stacking corners Natural aluminium	Fasteners Comfort fasteners	Handles Sprung drop handles	Integrated wheels Yes	Material Aluminium
Material of the stacking corners Aluminium	Seal foamed lid seal	Stacking corners Yes	Wheel diameter 50 mm	

Product variants

SKU 41810	SKU 41811	SKU 41812
Corner beading No	Corner beading Yes	Corner beading Yes
Internal dimensions L x W x H 516 mm × 350 mm × 159 mm	Internal dimensions L x W x H 550 mm × 350 mm × 310 mm	Internal dimensions L x W x H 750 mm × 350 mm × 380 mm
Max. gross weight dangerous goods permission 25 kg	Max. gross weight dangerous goods permission 25 kg	Max. gross weight dangerous goods permission 35 kg
Outside dimensions max. L x W x H 550 mm × 400 mm × 233 mm	Outside dimensions max. L x W x H 600 mm × 400 mm × 385 mm	Outside dimensions max. L x W x H 800 mm × 400 mm × 455 mm





Peripheral beading No	Peripheral beading Yes	Peripheral beading Yes
Pull handle 3-section	Pull handle 3-section	Pull handle 2-section
Total max. weight 25 kg	Total max. weight 25 kg	Total max. weight 35 kg
Volume 28 I	Volume 60 I	Volume 99 I
Weight 6.3 kg	Weight 7.3 kg	Weight 9 kg
SKU 41813	SKU 41814	SKU 41815
Corner beading Yes	Corner beading Yes	Corner beading Yes
Internal dimensions L x W x H 750 mm × 450 mm × 310 mm	Internal dimensions L x W x H 750 mm × 635 mm × 410 mm	Internal dimensions L x W x H 910 mm × 350 mm × 380 mm
Max. gross weight dangerous goods permission 35 kg	Max. gross weight dangerous goods permission 35 kg	Max. gross weight dangerous goods permission 50 kg
Outside dimensions max. L x W x H 800 mm × 500 mm × 385 mm	Outside dimensions max. L x W x H 800 mm × 685 mm × 485 mm	Outside dimensions max. L x W x H 960 mm × 400 mm × 455 mm
Peripheral beading Yes	Peripheral beading Yes	Peripheral beading Yes
Pull handle 2-section	Pull handle 2-section	Pull handle 2. Sprung drop handle
Total max. weight 35 kg	Total max. weight 35 kg	Total max. weight 50 kg
Volume	Volume	Volume







105 I	195 I	120 l
Weight	Weight	Weight
9.5 kg	12 kg	9.5 kg