



Lid for Mitraset Racklite

19" housing

Product description

- Elastic stacking elements on housing and lid corners.
- Lid equipped with 4 locking catches.
- Lids stiffened with moulded sections.
- Protection rating IP 65 in accordance with DIN EN 60529 and IEC 34-5/529 as a result of welded casing and lid with all-round seal.
- Wide range of special lids available on request.



Product features

Product variants

SKU	SKU	SKU
45933	45934	45935
Height lid	Height lid	Height lid
3 HE/U	4 HE/U	5 HE/U
Outside dimensions max. L x W x H	Outside dimensions max. L x W x H	Outside dimensions max. L x W x H
55 mm × 591 mm × 271,5 mm	55 mm × 591 mm × 316 mm	55 mm × 591 mm × 360,5 mm
Weight	Weight	Weight
2.2 kg	2.4 kg	2.6 kg



SKU 45936	SKU 45937	SKU 45938
Height lid 6 HE/U	Height lid 7 HE/U	Height lid 8 HE/U
Outside dimensions max. L x W x H 55 mm × 591 mm × 405 mm	Outside dimensions max. L x W x H 55 mm × 591 mm × 449,5 mm	Outside dimensions max. L x W x H 55 mm × 591 mm × 494 mm
Weight 2.7 kg	Weight 2.9 kg	Weight 3.1 kg
SKU 45939	SKU 45940	SKU 45941
Height lid 9 HE/U	Height lid 10 HE/U	Height lid 11 HE/U
Outside dimensions max. L x W x H 55 mm × 591 mm × 538,5 mm	Outside dimensions max. L x W x H 55 mm × 591 mm × 583 mm	Outside dimensions max. L x W x H 55 mm × 591 mm × 627,5 mm
Weight 3.3 kg	Weight 3.4 kg	Weight 3.6 kg
SKU 45942		
Height lid 12 HE/U		
Outside dimensions max. L x W x H 55 mm × 591 mm × 672 mm		
Weight 3.8 kg		