



MultiTower S-PLUS 1T, 2,50 m

The mobile scaffolding solution for quick and safe erection due to advanced guardrails, two-metre platform spacing and fewer individual parts.

Product description

- The mobile scaffolding solution for quick and safe erection due to advanced guardrails, two-metre platform spacing and fewer individual parts.
- Scaffolding width: 0.75 m; scaffolding length: 2.50 m.
- Safe and quick assembly and dismantling due to advanced guardrail (instead of railings and diagonal braces) and platforms at intervals of 2 m.
- Working heights can be extended from 3.35 m to max. 13.20 m with standard parts.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.
- Standard castors: height-adjustable 200 mm swivel castors (Order No. 42917) for millimetre-perfect level adjustment.



Hints and special features

Standard Z 600 mobile scaffold towers with stabilisers can also be retrofitted for stable set-up by adding the relevant S-PLUS single parts.

Product features

Claw type automatic	Height-adjustable castors: Yes	Platform length 2.5 m	Platform length 2.5 m	Platform size 0,6m × 2,5m
Platform width 0.6 m	Rung diameter 50 mm	Scaffolding class 3 (= 200 kg/m²)	Standards EN 1004-1	Stile diameter 50 mm
Warranty	Wheel diameter	Width scaffolding		



10 years

200 mm

0.75 m

Product variants

SKU 52226	SKU 52236	SKU 52246
Overall height 2.65 m	Overall height 3.75 m	Overall height 4.6 m
Platform height 1.4 m	Platform height 2.5 m	Platform height 3.35 m
Transport dimensions 2.800 mm × 900 mm × 400 mm	Transport dimensions 2.800 mm × 900 mm × 500 mm	Transport dimensions 2.800 mm × 900 mm × 600 mm
Weight 105.9 kg	Weight 132.5 kg	Weight 168.8 kg
Working height 3.4 m	Working height 4.5 m	Working height 5.35 m
SKU 52256	SKU 52266	SKU 52276
Overall height 5.7 m	Overall height 6.55 m	Overall height 7.65 m
Platform height 4.45 m	Platform height 5.3 m	Platform height 6.4 m
Transport dimensions 2.800 mm × 900 mm × 700 mm	Transport dimensions 2.800 mm × 900 mm × 800 mm	Transport dimensions 2.800 mm × 900 mm × 900 mm
Weight 182.8 kg	Weight 219.1 kg	Weight 233.1 kg
Working height 6.45 m	Working height 7.3 m	Working height 8.4 m



SKU 52286	SKU 52296	SKU 52306
Overall height 8.5 m	Overall height 9.65 m	Overall height 10.45 m
Platform height 7.25 m	Platform height 8.4 m	Platform height 9.2 m
Transport dimensions 2.800 mm × 900 mm × 1.000 mm	Transport dimensions 2.800 mm × 900 mm × 1.100 mm	Transport dimensions 2.800 mm × 900 mm × 1.200 mm
Weight 277.8 kg	Weight 291.8 kg	Weight 328.1 kg
Working height 9.25 m	Working height 10.4 m	Working height 11.2 m
SKU 52316	SKU 52326	
Overall height 11.6 m	Overall height 12.45 m	
Platform height 10.35 m	Platform height 11.2 m	
Transport dimensions 2.800 mm × 900 mm × 1.300 mm	Transport dimensions 2.800 mm × 900 mm × 1.400 mm	
Weight 342.1 kg	Weight 378.4 kg	
Working height 12.35 m	Working height 13.2 m	