



CompactMaster S-PLUS 1T

The top-selling folding scaffold unit is now available with advanced guardrail and two metre platform distance for safe and fast erection.

Product description

- The top-selling folding scaffold unit is now available with advanced guardrail and two metre platform distance for safe and fast erection.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding width: 0.85 m (to the outside edge of folding unit hinge); scaffolding length: 1.80 m.
- Working heights can be extended from 3.75 m to max. 13.55 m with standard parts.
- Scaffolding category 3 (maximum load of 200 kg/m²) according to DIN EN 1004.
- Standard castors: height-adjustable 150 mm swivel castors (order no. 42759) for millimetre-perfect level adjustment.



Product features

Claw type automatic	Platform length 1.8 m	Platform length 1.8 m	Platform size 0,6m x 1,8m	Platform width 0.6 m
Rung diameter 50 mm	Scaffolding class 3 (= 200 kg/m²)	Stile diameter 50 mm	Warranty 10 years	Width scaffolding 0.85 m

Product variants

SKU 53300	SKU 53099	SKU 53121
---------------------	---------------------	---------------------



Height-adjustable castors: No	Height-adjustable castors: Yes	Height-adjustable castors: Yes
Overall height 1.65 m	Overall height 3 m	Overall height 3.85 m
Platform height 0.95 m	Platform height 1.75 m	Platform height 2.6 m
Transport dimensions 1.900 mm x approx. 950 mm x approx. 480 mm	Standards EN 1004-1	Standards EN 1004-1
Weight 35.8 kg	Transport dimensions 0 mm0 mm0 mm	Transport dimensions 0 mm0 mm0 mm
Wheel diameter 125 mm	Weight 105.8 kg	Weight 123.6 kg
Working height 2.95 m	Wheel diameter 150 mm	Wheel diameter 150 mm
	Working height 3.75 m	Working height 4.6 m
SKU 53131	SKU 53141	SKU 53151
Height-adjustable castors: Yes	Height-adjustable castors: Yes	Height-adjustable castors: Yes
Overall height 4.95 m	Overall height 5.8 m	Overall height 6.9 m
Platform height 3.7 m	Platform height 4.55 m	Platform height 5.65 m
Standards EN 1004-1	Standards EN 1004-1	Standards EN 1004-1
Transport dimensions 0 mm0 mm0 mm	Transport dimensions 0 mm0 mm0 mm	Transport dimensions 0 mm0 mm0 mm



Weight 147.8 kg	Weight 165.6 kg	Weight 189.8 kg
Wheel diameter 150 mm	Wheel diameter 150 mm	Wheel diameter 150 mm
Working height 5.7 m	Working height 6.55 m	Working height 7.65 m
SKU 53161	SKU 53171	SKU 53181
Height-adjustable castors: Yes	Height-adjustable castors: Yes	Height-adjustable castors: Yes
Overall height 7.75 m	Overall height 8.9 m	Overall height 9.7 m
Platform height 6.5 m	Platform height 7.6 m	Platform height 8.4 m
Standards EN 1004-1	Standards EN 1004-1	Standards EN 1004-1
Transport dimensions 0 mm0 mm0 mm	Transport dimensions 0 mm0 mm0 mm	Transport dimensions 0 mm0 mm0 mm
Weight 216 kg	Weight 231.8 kg	Weight 249.6 kg
Wheel diameter 150 mm	Wheel diameter 150 mm	Wheel diameter 150 mm
Working height 8.5 m	Working height 9.6 m	Working height 10.45 m
SKU 53191	SKU 53101	SKU 53111
Height-adjustable castors:	Height-adjustable castors:	Height-adjustable castors:



Yes	Yes	Yes
Overall height 10.85 m	Overall height 11.7 m	Overall height 12.8 m
Platform height 9.6 m	Platform height 10.4 m	Platform height 11.55 m
Standards EN 1004-1	Standards EN 1004-1	Standards EN 1004-1
Transport dimensions 0 mm0 mm0 mm	Transport dimensions 0 mm0 mm0 mm	Transport dimensions 0 mm0 mm0 mm
Weight 273.8 kg	Weight 291.6 kg	Weight 315.8 kg
Wheel diameter 150 mm	Wheel diameter 150 mm	Wheel diameter 150 mm
Working height 11.6 m	Working height 12.4 m	Working height 13.55 m