



# CompactMaster S-PLUS 2T

The top-selling folding scaffold unit is now available with advanced guardrail and two metre platform distance for safe and fast erection.

## Product description

- Scaffolding width: 0.85 m or 1.45 m (lower section incl. hinges); Scaffolding length: 1.80 m.
- Working heights can be extended from 3.75 m to max. 13.55 m with standard parts.
- Basic module folds together for rapid erection and dismantling.
- Scaffolding category 3 (maximum load of 200 kg/m<sup>2</sup>) according to DIN EN 1004.
- Standard castors: height-adjustable 150 mm swivel castors (order no. 42759) for millimetre-perfect level adjustment.



## Product features

Claw type <b>automatic</b>	Fits through doorways <b>No</b>	Platform length <b>1.8 m</b>	Platform length <b>1.8 m</b>	Platform size <b>1,2m x 1,8m</b>
Platform width <b>1.2 m</b>	Rung diameter <b>50 mm</b>	Scaffolding class <b>3 (= 200 kg/m<sup>2</sup>)</b>	Stile diameter <b>50 mm</b>	Warranty <b>10 years</b>
Width scaffolding <b>1.45 m</b>				

## Product variants

SKU <b>53400</b>	SKU <b>53199</b>	SKU <b>53221</b>
Height-adjustable castors:	Height-adjustable castors:	Height-adjustable castors:



<b>No</b>	<b>Yes</b>	<b>Yes</b>
Overall height <b>1.65 m</b>	Overall height <b>3 m</b>	Overall height <b>3.85 m</b>
Platform height <b>0.95 m</b>	Platform height <b>1.75 m</b>	Platform height <b>2.6 m</b>
Transport dimensions <b>0 mm × 0 mm × 0 mm</b>	Transport dimensions <b>0 mm0 mm0 mm</b>	Transport dimensions <b>0 mm0 mm0 mm</b>
Weight <b>52.8 kg</b>	Weight <b>108.1 kg</b>	Weight <b>161.4 kg</b>
Wheel diameter <b>125 mm</b>	Wheel diameter <b>150 mm</b>	Wheel diameter <b>150 mm</b>
Working height <b>2.95 m</b>	Working height <b>3.75 m</b>	Working height <b>4.6 m</b>
SKU <b>53231</b>	SKU <b>53241</b>	SKU <b>53251</b>
Height-adjustable castors: <b>Yes</b>	Height-adjustable castors: <b>Yes</b>	Height-adjustable castors: <b>Yes</b>
Overall height <b>4.95 m</b>	Overall height <b>5.8 m</b>	Overall height <b>6.9 m</b>
Platform height <b>3.7 m</b>	Platform height <b>4.55 m</b>	Platform height <b>5.65 m</b>
Transport dimensions <b>0 mm0 mm0 mm</b>	Transport dimensions <b>0 mm0 mm0 mm</b>	Transport dimensions <b>0 mm0 mm0 mm</b>
Weight <b>189.4 kg</b>	Weight <b>225 kg</b>	Weight <b>250.7 kg</b>
Wheel diameter <b>150 mm</b>	Wheel diameter <b>150 mm</b>	Wheel diameter <b>150 mm</b>



Working height <b>5.7 m</b>	Working height <b>6.55 m</b>	Working height <b>7.65 m</b>
SKU <b>53261</b>	SKU <b>53271</b>	SKU <b>53281</b>
Height-adjustable castors: <b>Yes</b>	Height-adjustable castors: <b>Yes</b>	Height-adjustable castors: <b>Yes</b>
Overall height <b>7.75 m</b>	Overall height <b>8.9 m</b>	Overall height <b>9.7 m</b>
Platform height <b>6.5 m</b>	Platform height <b>7.6 m</b>	Platform height <b>8.4 m</b>
Transport dimensions <b>0 mm0 mm0 mm</b>	Transport dimensions <b>0 mm0 mm0 mm</b>	Transport dimensions <b>0 mm0 mm0 mm</b>
Weight <b>284 kg</b>	Weight <b>312 kg</b>	Weight <b>345.3 kg</b>
Wheel diameter <b>150 mm</b>	Wheel diameter <b>150 mm</b>	Wheel diameter <b>150 mm</b>
Working height <b>8.5 m</b>	Working height <b>9.6 m</b>	Working height <b>10.45 m</b>
SKU <b>53291</b>	SKU <b>53201</b>	SKU <b>53211</b>
Height-adjustable castors: <b>Yes</b>	Height-adjustable castors: <b>Yes</b>	Height-adjustable castors: <b>Yes</b>
Overall height <b>10.85 m</b>	Overall height <b>11.7 m</b>	Overall height <b>12.8 m</b>
Platform height <b>9.6 m</b>	Platform height <b>10.4 m</b>	Platform height <b>11.55 m</b>
Transport dimensions	Transport dimensions	Transport dimensions



0 mm0 mm0 mm	0 mm0 mm0 mm	0 mm0 mm0 mm
Weight <b>373.3 kg</b>	Weight <b>406.6 kg</b>	Weight <b>434.6 kg</b>
Wheel diameter <b>150 mm</b>	Wheel diameter <b>150 mm</b>	Wheel diameter <b>150 mm</b>
Working height <b>11.6 m</b>	Working height <b>12.4 m</b>	Working height <b>13.55 m</b>