




Saferstep L

The high non-slip performance of Safer Step Technology makes for comfortable and safe use, while the anodised stiles are wear-resistant and pleasant to hold.

Product description

- The high non-slip performance of Safer Step Technology makes for comfortable and safe use, while the anodised stiles are wear-resistant and pleasant to hold.
- Also available as a shelf-ladder.
- Tread with ZARGES Safer Step Technology, 80 mm deep.
- Abrasion-resistant, anodised stiles.
- Overall width: 420 mm.
- High strength, non-twist rung/stile connections.
- Treads and stiles made from extruded aluminium sections.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



Hints and special features

Complies with EN 131 Professional.

Product features

Coating anodised	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium	Pitch rung/tread 265 mm
Standards EN 131 professional	Stile depth 68 mm	Tread depth 80 mm	Type rung/tread Safer Step	Warranty 10 years

Product variants



SKU 41356	SKU 41358	SKU 41360
Number of treads 6	Number of treads 8	Number of treads 10
Overall length 1.94 m	Overall length 2.5 m	Overall length 3.06 m
Transport dimensions 1.930 mm × 420 mm × approx. 80 mm	Transport dimensions 2.490 mm × 420 mm × approx. 80 mm	Transport dimensions 3.050 mm × 420 mm × approx. 80 mm
Weight 5 kg	Weight 6.5 kg	Weight 8.8 kg
Working height 2.8 m	Working height 3.35 m	Wide crosspiece 0.8 m
		Working height 3.85 m
SKU 41362	SKU 41364	SKU 41366
Number of treads 12	Number of treads 14	Number of treads 16
Overall length 3.62 m	Overall length 4.18 m	Overall length 4.74 m
Transport dimensions 3.610 mm × 420 mm × approx. 80 mm	Transport dimensions 4.170 mm × 420 mm × approx. 80 mm	Transport dimensions 4.730 mm × 420 mm × approx. 80 mm
Weight 10.3 kg	Weight 11.8 kg	Weight 13.3 kg
Wide crosspiece 0.8 m	Wide crosspiece 0.89 m	Wide crosspiece 0.89 m
Working height	Working height	Working height



4.4 m

4.9 m

5.45 m