



Seventec L

The deep treads and 7-point tread-stile connection ensure a high degree of comfort, safe standing and extremely high stability.

Product description

- The deep treads and 7-point tread-stile connection ensure a high degree of comfort, safe standing and extremely high stability.
- Smooth external stile surfaces that are comfortable to hold.
- Treads 85 mm deep and with safe, non-slip serrated surfaces.
- Outside width: 400 mm.
- Especially light and easy to carry.
- 7-point connection between tread and stile with reinforcement in the centre of the tread.
- Treads and stiles made from extruded aluminium sections.
- Inside width: 360 mm.



Hints and special features

in accordance with DIN EN 131-1, order No. 40384 includes a stabiliser bar.
 Complies with EN 131 Professional.

Product features

Coating natural	Connection Stile-Rung riveted	Load capacity max. 150 kg	Material Aluminium	Pitch rung/tread 218 mm
Standards EN 131 professional	Stile depth 87 mm	Tread depth 85 mm	Type rung/tread serrated	Warranty 10 years

Product variants



SKU 40378	SKU 40380	SKU 40382
Number of treads 8	Number of treads 10	Number of treads 12
Overall length 2.08 m	Overall length 2.54 m	Overall length 2.99 m
Transport dimensions 2.090 mm × 400 mm × 90 mm	Transport dimensions 2.550 mm × 400 mm × 90 mm	Transport dimensions 3.010 mm × 400 mm × 90 mm
Weight 5.8 kg	Weight 7.2 kg	Weight 8.5 kg
Working height 3.05 m	Working height 3.45 m	Working height 3.9 m
SKU 40384		
Number of treads 14		
Overall length 3.42 m		
Transport dimensions 3.470 mm × 400 mm × 90 mm		
Weight 11.4 kg		
Wide crosspiece 0.8 m		
Working height 4.35 m		