

Strato DL

The inexpensive alternative for safe ascent and quick and flexible application.

Product description

- The inexpensive alternative for safe ascent and quick and flexible application.
- Robust extruded-section triangular rungs with step horizontal in working position.
- Outside width: 350 mm.
- Special rung design creates a broad step area.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- High strength, non-twist rung/stile connections.



Hints and special features

Complies with EN 131 Professional.

Product features


Coating natural	Connection Stile-Rung flanged	Load capacity max. 150 kg	Material Aluminium	Pitch rung/tread 265 mm
Standards EN 131 professional	Tread depth 38 mm	Type rung/tread serrated	Warranty 10 years	

Product variants

SKU 44808	SKU 44810	SKU 44812
Number of rungs 8	Number of rungs 10	Number of rungs 12



Overall length 2.42 m	Overall length 2.98 m	Overall length 3.54 m
Stile depth 58 mm	Stile depth 58 mm	Stile depth 68 mm
Transport dimensions 2.420 mm × 360 mm × 60 mm	Transport dimensions 2.980 mm × 360 mm × 60 mm	Transport dimensions 3.540 mm × 360 mm × 70 mm
Weight 4.3 kg	Weight 5.3 kg	Weight 7.9 kg
Working height 3.3 m	Working height 3.85 m	Wide crosspiece 0.79 m
		Working height 4.4 m
SKU 44814	SKU 44816	SKU 44818
Number of rungs 14	Number of rungs 16	Number of rungs 18
Overall length 4.11 m	Overall length 4.67 m	Overall length 5.23 m
Stile depth 73 mm	Stile depth 73 mm	Stile depth 73 mm
Transport dimensions 4.110 mm × 360 mm × 75 mm	Transport dimensions 4.660 mm × 360 mm × 75 mm	Transport dimensions 5.220 mm × 360 mm × 75 mm
Weight 9.2 kg	Weight 10.1 kg	Weight 11.2 kg
Wide crosspiece 0.79 m	Wide crosspiece 0.89 m	Wide crosspiece 0.89 m
Working height 4.9 m	Working height 5.45 m	Working height 6 m



SKU		
44819		
Number of rungs		
20		
Overall length		
5.9 m		
Stile depth		
73 mm		
Transport dimensions		
5.780 mm × 360 mm × 75 mm		
Weight		
12.4 kg		
Wide crosspiece		
0.99 m		
Working height		
6.55 m		