



Comfortstep Trec LH

For easy travel backwards and forwards along your shelving: The solution with guide rails and self-locking sprung castors is individually height-adjustable.

Product description

- For easy travel backwards and forwards along your shelving: The solution with guide rails and self-locking sprung castors is individually height-adjustable.
- Both the top of the ladder and the self-locking sprung castors at the bottom lock the shelf ladder when weight is applied.
- When not in use, the ladder can be stowed vertically on the shelf to save space.



Hints and special features

Please quote the distance between the floor and the top edge of the tubular rail when ordering!
 Complies with EN 131 Professional.



Product features

Coating anodised	Connection Stile-Rung bolted	Load capacity max. 150 kg	Material Aluminium	Pitch rung/tread 250 mm
Standards EN 131 professional	Tread depth 80 mm	Type rung/tread padding on front tread edges	Warranty 10 years	

Product variants

SKU 41412	SKU 41413	SKU 41414
---------------------	---------------------	---------------------



Height hook on vertical =1,84m-=2,08 m	Height hook on vertical =2,09m-=2,33 m	Height hook on vertical =2,34m-=2,58 m
Max height hook on vertical 2.08 m	Max height hook on vertical 2.33 m	Max height hook on vertical 2.58 m
Min height hook on vertical 1.84 m	Min height hook on vertical 2.09 m	Min height hook on vertical 2.34 m
Number of treads 6	Number of treads 7	Number of treads 8
Transport dimensions 1.680 mm × 380 mm × 100 mm	Transport dimensions 1.920 mm × 380 mm × 100 mm	Transport dimensions 2.160 mm × 380 mm × 100 mm
Weight 4.5 kg	Weight 5.2 kg	Weight 5.9 kg
Working height 2.75 m	Working height 3 m	Working height 3.25 m
SKU 41415	SKU 41416	
Height hook on vertical =2,59m-=2,83 m	Height hook on vertical =2,84m-=3,08 m	
Max height hook on vertical 2.83 m	Max height hook on vertical 3.08 m	
Min height hook on vertical 2.59 m	Min height hook on vertical 2.84 m	
Number of treads 9	Number of treads 10	
Transport dimensions 2.400 mm × 380 mm × 100 mm	Transport dimensions 2.640 mm × 380 mm × 100 mm	
Weight 6.6 kg	Weight 7.6 kg	



Working height

3.5 m

Working height

3.75 m