



# Everest 2E

The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.

## Product description

- The convenient solution for working at great heights with maximum ladder width for comfortable climbing and safe standing.
- From length of 8.30 m – upper ladder with wheel assemblies. Wall wheels with wear-resistant surfaces that will not damage the wall.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 40245-40247
- A high level of stability thanks to extra-wide bottom ladder (490 mm).
- Plastic anti-friction insert and lift-off retainer.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



## Hints and special features

Complies with EN 131 Professional.

## Product features

Coating <b>natural</b>	Connection Stile-Rung <b>flanged</b>	External width of lower ladder <b>490 mm</b>	Load capacity <b>max. 150 kg</b>	Material <b>Aluminium</b>
Pitch rung/tread <b>270 mm</b>	Standards <b>EN 131 professional</b>	Tread depth <b>30 mm</b>	Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>
Wheels <b>Rubber</b>				



## Product variants

SKU <b>40245</b>	SKU <b>40246</b>	SKU <b>40247</b>
Number of rungs <b>2 x 6</b>	Number of rungs <b>2 x 8</b>	Number of rungs <b>2 x 10</b>
Overall length, extended <b>2.95 m</b>	Overall length, extended <b>4.07 m</b>	Overall length, extended <b>4.96 m</b>
Overall length, retracted <b>1.83 m</b>	Overall length, retracted <b>2.39 m</b>	Overall length, retracted <b>3 m</b>
Stile depth <b>58 mm</b>	Stile depth <b>68 mm</b>	Stile depth <b>68 mm</b>
Transport dimensions <b>1.830 mm x 500 mm x 130 mm</b>	Transport dimensions <b>2.390 mm x 500 mm x 130 mm</b>	Transport dimensions <b>3.000 mm x 500 mm x 140 mm</b>
Weight <b>7.6 kg</b>	Weight <b>9.8 kg</b>	Weight <b>13.5 kg</b>
Working height <b>3.8 m</b>	Wide crosspiece <b>0.9 m</b>	Wide crosspiece <b>1 m</b>
	Working height <b>4.85 m</b>	Working height <b>5.75 m</b>
SKU <b>40248</b>	SKU <b>40249</b>	SKU <b>40214</b>
Number of rungs <b>2 x 12</b>	Number of rungs <b>2 x 14</b>	Number of rungs <b>2 x 16</b>
Overall length, extended <b>6.09 m</b>	Overall length, extended <b>7.21 m</b>	Overall length, extended <b>8.33 m</b>
Overall length, retracted <b>3.56 m</b>	Overall length, retracted <b>4.07 m</b>	Overall length, retracted <b>4.7 m</b>



Stile depth <b>73 mm</b>	Stile depth <b>85 mm</b>	Stile depth <b>98 mm</b>
Transport dimensions <b>3.570 mm × 500 mm × 160 mm</b>	Transport dimensions <b>4.130 mm × 500 mm × 160 mm</b>	Transport dimensions <b>4.690 mm × 500 mm × 180 mm</b>
Weight <b>18 kg</b>	Weight <b>19.5 kg</b>	Weight <b>26.2 kg</b>
Wide crosspiece <b>1.1 m</b>	Wide crosspiece <b>1.2 m</b>	Wide crosspiece <b>1.2 m</b>
Working height <b>6.8 m</b>	Working height <b>7.9 m</b>	Working height <b>9 m</b>
SKU <b>40215</b>	SKU <b>40216</b>	SKU <b>40217</b>
Number of rungs <b>2 × 18</b>	Number of rungs <b>2 × 20</b>	Number of rungs <b>2 × 24</b>
Overall length, extended <b>9.13 m</b>	Overall length, extended <b>10.25 m</b>	Overall length, extended <b>12.22 m</b>
Overall length, retracted <b>5.2 m</b>	Overall length, retracted <b>5.74 m</b>	Overall length, retracted <b>6.9 m</b>
Stile depth <b>98 mm</b>	Stile depth <b>114 mm</b>	Stile depth <b>114 mm</b>
Transport dimensions <b>5.210 mm × 500 mm × 230 mm</b>	Transport dimensions <b>5.770 mm × 500 mm × 230 mm</b>	Transport dimensions <b>6.900 mm × 500 mm × 230 mm</b>
Weight <b>28.8 kg</b>	Weight <b>33 kg</b>	Weight <b>41.5 kg</b>
Wide crosspiece <b>1.2 m</b>	Wide crosspiece <b>1.2 m</b>	Wide crosspiece <b>1.2 m</b>
Working height <b>9.75 m</b>	Working height <b>10.85 m</b>	Working height <b>12.75 m</b>

