



## Everest 2DE

Safe, flexible and suitable for great heights, with an excellent price/performance ratio.

### Product description

- Safe, flexible and suitable for great heights, with an excellent price/performance ratio.
- Convenient and precise rung-by-rung height adjustment in a grid of 280 mm.
- Both parts of the ladder can also be used separately as single ladders for Order Nos. 44834 and 44820
- Robust extruded-section triangular rungs with step horizontal in working position.
- External width of lower ladder: 420 mm.
- Positive-locking extruded aluminium section guide fittings.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



### Hints and special features

Complies with EN 131 Professional.

### Product features

|                                   |   |   |                                     |                              |
|-----------------------------------|---|---|-------------------------------------|------------------------------|
| Coating<br><b>natural</b>         | Connection Stile-Rung<br><b>flanged</b> | External width of lower ladder<br><b>420 mm</b> | Load capacity<br><b>max. 150 kg</b> | Material<br><b>Aluminium</b> |
| Pitch rung/tread<br><b>265 mm</b> | Standards<br><b>EN 131 professional</b> | Tread depth<br><b>38 mm</b>                     | Type rung/tread<br><b>serrated</b>  | Warranty<br><b>10 years</b>  |

### Product variants

|     |     |     |
|-----|-----|-----|
| SKU | SKU | SKU |
|-----|-----|-----|



|   |   |   |
|---|---|---|
| <b>44834</b>  | <b>44820</b>  | <b>44822</b>  |
| Number of rungs<br><b>2 x 8</b>                           | Number of rungs<br><b>2 x 10</b>                          | Number of rungs<br><b>2 x 12</b>                          |
| Overall length, extended<br><b>3.8 m</b>                  | Overall length, extended<br><b>4.93 m</b>                 | Overall length, extended<br><b>6.05 m</b>                 |
| Overall length, retracted<br><b>2.42 m</b>                | Overall length, retracted<br><b>2.98 m</b>                | Overall length, retracted<br><b>3.54 m</b>                |
| Stile depth<br><b>58 mm</b>                               | Stile depth<br><b>68 mm</b>                               | Stile depth<br><b>68 mm</b>                               |
| Transport dimensions<br><b>2.420 mm x 420 mm x 115 mm</b> | Transport dimensions<br><b>2.980 mm x 430 mm x 120 mm</b> | Transport dimensions<br><b>3.540 mm x 430 mm x 135 mm</b> |
| Weight<br><b>9.3 kg</b>                                   | Weight<br><b>11.3 kg</b>                                  | Weight<br><b>15.4 kg</b>                                  |
| Wide crosspiece<br><b>0.8 m</b>                           | Wide crosspiece<br><b>0.9 m</b>                           | Wide crosspiece<br><b>1 m</b>                             |
| Working height<br><b>4.6 m</b>                            | Working height<br><b>5.65 m</b>                           | Working height<br><b>6.8 m</b>                            |
| SKU<br><b>44824</b>                                       | SKU<br><b>44826</b>                                       | SKU<br><b>44828</b>                                       |
| Number of rungs<br><b>2 x 14</b>                          | Number of rungs<br><b>2 x 16</b>                          | Number of rungs<br><b>2 x 18</b>                          |
| Overall length, extended<br><b>7.17 m</b>                 | Overall length, extended<br><b>8.29 m</b>                 | Overall length, extended<br><b>9.17 m</b>                 |
| Overall length, retracted<br><b>4.1 m</b>                 | Overall length, retracted<br><b>4.66 m</b>                | Overall length, retracted<br><b>5.23 m</b>                |
| Stile depth<br><b>85 mm</b>                               | Stile depth<br><b>85 mm</b>                               | Stile depth<br><b>85 mm</b>                               |



|   |   |   |
|---|---|---|
| Transport dimensions<br><b>4.100 mm × 430 mm × 135 mm</b> | Transport dimensions<br><b>4.660 mm × 430 mm × 145 mm</b> | Transport dimensions<br><b>5.230 mm × 430 mm × 145 mm</b> |
| Weight<br><b>17.8 kg</b>                                  | Weight<br><b>21.5 kg</b>                                  | Weight<br><b>23.9 kg</b>                                  |
| Wide crosspiece<br><b>1.1 m</b>                           | Wide crosspiece<br><b>1.2 m</b>                           | Wide crosspiece<br><b>1.2 m</b>                           |
| Working height<br><b>7.85 m</b>                           | Working height<br><b>8.7 m</b>                            | Working height<br><b>9.8 m</b>                            |