



## **Skyline 3E**

When you need access to great heights: Optimised transport dimensions, working heights of up to 14.70 m with convenient height adjustment.

## **Product description**

- When you need access to great heights: Optimised transport dimensions, working heights of up to 14.70 m with convenient height adjustment.
- Wheel assemblies with abrasion-resistant surfaces that will not damage the wall.
- Two ropes so that centre and top sections can be adjusted separately.
- · Rung-by-rung height adjustment in a grid of 280 mm.
- The ladder with the Order No. 40448 is equipped with 2 light alloy supports for easy erection and stabilisation. (Not to be used as free-standing ladders!)
- Locks securely thanks to automatic spring loaded pawls.
- Improved plastic guide.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.
- Rungs and stiles made from extruded aluminium sections.



Complies with EN 131 Professional.

## **Product features**

Coating	Connection Stile-Rung	Load capacity	Material	Pitch rung/tread
natural	flanged	max. 150 kg	Aluminium	270 mm
Standards	Stile depth	Tread depth	Type rung/tread	Warranty
EN 131 professional	98 mm	30 mm	serrated	10 years











Wheels

Wide crosspiece

Rubber

1.2 m

## **Product variants**

SKU 40446	SKU 40447	SKU 40448
External width of lower ladder  560 mm	External width of lower ladder  560 mm	External width of lower ladder  590 mm
Number of rungs  3 × 15	Number of rungs 3 × 18	Number of rungs  3 × 20
Overall length, extended  10.55 m	Overall length, extended  12.55 m	Overall length, extended  14.2 m
Overall length, retracted 4.4 m	Overall length, retracted 5.25 m	Overall length, retracted  5.8 m
Stile depth 86mm / 98mm	Stile depth 86mm / 98mm	Stile depth 98mm / 98mm
Transport dimensions 4.420 mm × 565 mm × 228 mm	Transport dimensions 5.260 mm × 565 mm × 228 mm	Transport dimensions 5.820 mm × 718 mm × 242 mm
Weight 45 kg	Weight 53 kg	Weight 68 kg
Working height 11.15 m	Working height 13.1 m	Working height 14.7 m