



# Skyline EFA 2E

For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.

## Product description

- For special applications at great heights: the special ladder for working in high-voltage or chemical environments, with convenient height adjustment.
- Stiles and rungs made of glass-fibre-reinforced plastic for particularly high chemical resistance.
- Complies with the high-voltage test for ladders of insulating material in accordance with DIN EN 61 478 or VDE 0682 Section 6.5 Category 1/30 KV.
- Suitable for working in high-voltage environments (1000 V AC, 1500 V DC).
- Very easy and convenient rung-by-rung height adjustment in a 280 mm grid via synthetic rope and roller.
- Wall wheels that will not damage the wall.
- Stiles and rungs (30 mm x 30 mm) made from glass-fibre-reinforced plastic for particularly high chemical resistance.
- Resistance to ageing in accordance with DIN EN ISO 4892-2.
- Overall width of bottom section: 430 mm.
- Replaceable 2-component plastic end caps ensure secure positioning without the risk of slipping.



## Hints and special features

Complies with EN 131 Professional.

## Product features

External width of lower ladder <b>420 mm</b>	Load capacity <b>max. 150 kg</b>	Material <b>Glass-fibre reinforced plastic</b>	Pitch rung/tread <b>270 mm</b>	Standards <b>EN 131 professional</b>
---	-------------------------------------	---	-----------------------------------	---



Stile depth <b>90 mm</b>	Tread depth <b>30 mm</b>	Type rung/tread <b>serrated</b>	Warranty <b>10 years</b>	Wheels <b>Rubber</b>
-----------------------------	-----------------------------	------------------------------------	-----------------------------	-------------------------

## Product variants

SKU <b>41274</b>	SKU <b>41276</b>
Number of rungs <b>2 x 14</b>	Number of rungs <b>2 x 16</b>
Overall length, extended <b>7.17 m</b>	Overall length, extended <b>7.72 m</b>
Overall length, retracted <b>4.09 m</b>	Overall length, retracted <b>4.64 m</b>
Transport dimensions <b>4.100 mm x 470 mm x 150 mm</b>	Transport dimensions <b>4.650 mm x 450 mm x 150 mm</b>
Weight <b>35.7 kg</b>	Weight <b>41.3 kg</b>
Wide crosspiece <b>1.1 m</b>	Wide crosspiece <b>1.2 m</b>
Working height <b>7.95 m</b>	Working height <b>8.5 m</b>