



Comfortstep S

Protection for your shins: high degree of comfort while working through padded treads.

Product description

- Protection for your shins: high degree of comfort while working through padded treads.
- Deep treads with padded front edge for standing comfort.
- Large platform that allows personnel to stand safely and comfortably even when working for extended periods.
- 80 mm deep treads with padded front edges.
- · Abrasion-resistant, anodised stiles.
- Platform made from extruded aluminium (300 mm × 250 mm) for safe and comfortable standing even when working for longer periods of time.
- Practical aluminium storage tray for small items and tools
- High-strength Perlon belts prevent splay, fitted on all models of 4 rungs or more.
- Treads with plastic-cushioned front edges.
- Screwed connection between treads and stile.
- Treads and stiles made from extruded aluminium sections.

Hints and special features

Complies with EN 131 Professional.

Product features

Coating anodised	Connection Stile-Rung bolted	Load capacity max. 150 kg	Material Aluminium	Pitch rung/tread 250 mm
Platform length 250 mm	Platform width 300 mm	Standards EN 131 professional	Stile depth 42 mm	Tray Aluminium







Tread depth **80 mm**

Type rung/tread

padding on front tread edges

Warranty

10 years

Product variants

SKU 41421	SKU 41422	SKU 41423
Base 0,75 m × 0,5 m	Anti splay Belt strap	Anti splay Belt strap
Number of rungs, incl. platform 3	Base 0,92 m × 0,53 m	Base 1,09 m × 0,56 m
Overall base width 0.5 m	Number of rungs, incl. platform 4	Number of rungs, incl. platform 5
Overall length 1.52 m	Overall base width 0.53 m	Overall base width 0.56 m
Platform height 0.75 m	Overall length 1.79 m	Overall length 2.06 m
Stile depth 42 mm	Platform height 1 m	Platform height 1.25 m
Stile depth steps/back stay 42mm / 42mm	Stile depth 42 mm	Stile depth 42 mm
Transport dimensions 1.520 mm × 500 mm × 150 mm	Stile depth steps/back stay 42mm / 42mm	Stile depth steps/back stay 42mm / 42mm
Vertical ladder height 1.38 m	Transport dimensions 1.790 mm × 530 mm × 150 mm	Transport dimensions 2.060 mm × 560 mm × 150 mm
Weight 6.4 kg	Vertical ladder height 1.63 m	Vertical ladder height 1.88 m
Working height	Weight	Weight





2.75 m	7.4 kg	8.4 kg
	Working height 3 m	Working height 3.25 m
SKU 41424	SKU 41425	SKU 41426
Anti splay Belt strap	Anti splay Belt strap	Anti splay Belt strap
Base 1,27 m × 0,59 m	1,44 m × 0,61 m	1,61 m × 0,64 m
Number of rungs, incl. platform 6	Number of rungs, incl. platform 7	Number of rungs, incl. platform
Overall base width 0.59 m	Overall base width 0.61 m	Overall base width 0.64 m
Overall length 2.33 m	Overall length 2.6 m	Overall length 2.87 m
Platform height 1.5 m	Platform height 1.75 m	Platform height 2 m
Stile depth 48 mm	Stile depth 48 mm	Stile depth 48 mm
Stile depth steps/back stay 48mm / 42mm	Stile depth steps/back stay 48mm / 42mm	Stile depth steps/back stay 48mm / 42mm
Transport dimensions 2.330 mm × 590 mm × 150 mm	Transport dimensions 2.600 mm × 615 mm × 150 mm	Transport dimensions 2.870 mm × 640 mm × 150 mm
Vertical ladder height 2.13 m	Vertical ladder height 2.38 m	Vertical ladder height 2.63 m
Weight 9.7 kg	Weight 10.7 kg	Weight 11.9 kg



4 m





Working height 3.5 m SKU 41427 Anti splay **Belt strap** Base $1,95 \text{ m} \times 0,7 \text{ m}$ Number of rungs, incl. platform 10 Overall base width 0.7 m Overall length 3.4 m Platform height 2.5 m Stile depth 48 mm Stile depth steps/back stay 48mm / 42mm Transport dimensions 3.410 mm × 700 mm × 150 mm Vertical ladder height 3.13 m Weight 14.4 kg Working height

Working height Working height

3.75 m

ZARGES GmbH Tel: +49 (0)881-687-100 Zargesstraße 7 Fax: +49 (0)881-687-500

www.zarges.com zarges@zarges.de

4.5 m







82362 Weilheim